

IECEX BAS 15.0108X
Baseefa15ATEX0163X



Schedule Drawing

S Harrison

REVISIONS		
REV.	DESCRIPTION	DATE
A		2015-12-08
B	UPDATED MATRIX	2015-12-08

Frame variant Manufactured from material with a minimum tensile strength of 340 N/mm ²	Equipment certified	Open ended variation Suffixed 'O'	Back to back variation suffixed 'btb'	'O' and 'btb' variation	Bolted	Welded
RGG	X	X			X	X
RGSFB 60mm wide x 10mm thick flat bar	X	X	X	X	X	X
RGSCFB	X	X	X		X	X
RGSKFB	X	X			X	X
RGSRFB	X	X	X		X	X

Ritad Drawn	Kontr. Check	Granskad Reviewed	Godkänd Approved	Tolerans, dir. ej annat anges Tolerance unless stated	Enhet, nr Assembly/drawing no.	Erstat Replaces	E VKT Mögl.
AK 151208	AK 151208	JF 151208	BJ 151208	Yttermat. dir. ej annat anges Surface finish, otherwise not stated	Material	Erstat Replaces	E VKT Mögl.



MATRIX
EQUIPMENT APPROVED
ATEX / IECEX FRAMES

Ritn. nr. Draw no.	Rev.
1160008	B